

Order form

LF1-2-3 fixed or withdrawable for MC cassette (IEC standard)

Only one of the boxes (ticked or filled) by the needed value) have to be considered between each horizontal line.
Blue box corresponds to none priced functions.

Basic circuit breaker		Quantity
Circuit breaker type		
	LF1 <input type="checkbox"/> LF2 <input type="checkbox"/> LF3 <input type="checkbox"/>	
	fixed <input type="checkbox"/> withdrawable for MC cassette <input type="checkbox"/>	
Rated voltage Ur	(kV)	<input type="text"/>
Impulse voltage Up	(kVbil)	<input type="text"/>
Breaking current Isc	(kA)	<input type="text"/>
Rated current Ir	(A)	<input type="text"/>
Frequency	50 Hz <input type="checkbox"/> 60 Hz <input type="checkbox"/>	
Operating sequence	O-0.3s-CO-15s-CO <input type="checkbox"/> O-0.3s-CO-3mn-CO <input type="checkbox"/> O-3mn-CO-3mn-CO <input type="checkbox"/>	
Colour for push buttons and indicators		
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
Push buttons open/close:	red/black red/green green/red red/black (ANSI)	
Indicator open/close:	black/white black/white green/red green/red	
Operating mechanism indicator charged/discharged:	white/yellow white/yellow charge/discharge charge/discharge	
1st opening release * (see possible choice in combination table)		
Shunt		
24 Vdc <input type="checkbox"/>	60 Vdc <input type="checkbox"/>	220 Vdc <input type="checkbox"/> 220 Vac (50 Hz) <input type="checkbox"/>
30 Vdc <input type="checkbox"/>	110 Vdc <input type="checkbox"/>	48 Vac (50 Hz) <input type="checkbox"/> 120 Vac (60 Hz) <input type="checkbox"/>
48 Vdc <input type="checkbox"/>	125 Vdc <input type="checkbox"/>	110 Vac (50 Hz) <input type="checkbox"/> 240 Vac (60 Hz) <input type="checkbox"/>
Undervoltage		
24 Vdc <input type="checkbox"/>	60 Vdc <input type="checkbox"/>	220 Vdc <input type="checkbox"/> 220 Vac (50 Hz) <input type="checkbox"/>
30 Vdc <input type="checkbox"/>	110 Vdc <input type="checkbox"/>	48 Vac (50 Hz) <input type="checkbox"/> 120 Vac (60 Hz) <input type="checkbox"/>
48 Vdc <input type="checkbox"/>	125 Vdc <input type="checkbox"/>	110 Vac (50 Hz) <input type="checkbox"/> 240 Vac (60 Hz) <input type="checkbox"/>
Downstream supply (only AC)		
Mitop (not available with seismic version)		
	without contact <input type="checkbox"/>	with contact <input type="checkbox"/>
Closing release	24 Vdc <input type="checkbox"/> 60 Vdc <input type="checkbox"/> 220 Vdc <input type="checkbox"/> 220 Vac (50 Hz) <input type="checkbox"/>	
	30 Vdc <input type="checkbox"/> 110 Vdc <input type="checkbox"/> 48 Vac (50 Hz) <input type="checkbox"/> 120 Vac (60 Hz) <input type="checkbox"/>	
	48 Vdc <input type="checkbox"/> 125 Vdc <input type="checkbox"/> 110 Vac (50 Hz) <input type="checkbox"/> 240 Vac (60 Hz) <input type="checkbox"/>	
Electrical operating mechanism	24...32 Vdc <input type="checkbox"/> 110...127 Vdc/ac <input type="checkbox"/>	
	48...60 Vdc/ac <input type="checkbox"/> 220...250 Vdc/ac <input type="checkbox"/>	
Leaflets language	French <input type="checkbox"/> English <input type="checkbox"/>	
Options		
2nd opening release * (see possible choice in combination table)		
Shunt		
24 Vdc <input type="checkbox"/>	60 Vdc <input type="checkbox"/>	220 Vdc <input type="checkbox"/> 220 Vac (50 Hz) <input type="checkbox"/>
30 Vdc <input type="checkbox"/>	110 Vdc <input type="checkbox"/>	48 Vac (50 Hz) <input type="checkbox"/> 120 Vac (60 Hz) <input type="checkbox"/>
48 Vdc <input type="checkbox"/>	125 Vdc <input type="checkbox"/>	110 Vac (50 Hz) <input type="checkbox"/> 240 Vac (60 Hz) <input type="checkbox"/>
Undervoltage		
24 Vdc <input type="checkbox"/>	60 Vdc <input type="checkbox"/>	220 Vdc <input type="checkbox"/> 220 Vac (50 Hz) <input type="checkbox"/>
30 Vdc <input type="checkbox"/>	110 Vdc <input type="checkbox"/>	48 Vac (50 Hz) <input type="checkbox"/> 120 Vac (60 Hz) <input type="checkbox"/>
48 Vdc <input type="checkbox"/>	125 Vdc <input type="checkbox"/>	110 Vac (50 Hz) <input type="checkbox"/> 240 Vac (60 Hz) <input type="checkbox"/>
Downstream supply (only AC)		
Mitop (not available with seismic version)		
	without contact <input type="checkbox"/>	with contact <input type="checkbox"/>
LV connection	male plug (1.2 m) (only fixed version) <input type="checkbox"/>	female socket (2 m) <input type="checkbox"/>
Locking CB in open position (only fixed version)	Ronis <input type="checkbox"/>	Profalux <input type="checkbox"/>
Sismic version (consult us)		<input type="checkbox"/>
Accessories		
Support frame (only fixed version)		<input type="checkbox"/>

(*) Different releases combinations

Shunt	1		2	1	1
Mitop		1		1	1
Undervoltage			1	1	1